



^Disc type

- UHD Blu-ray, Blu-ray, Blu-ray 3D, DVD-Video, DVD-Audio, AVCHD, SACD, CD, Kodak Picture CD, CD-R/RW, DVD±R/RW, DVD±R DL, BD-R/RE

^Output

- Analog Audio Output: 7.1 channel RCA, 2 channel RCA and Balanced XLR
- Digital Audio Output: Optical, Coaxial, HDMI
- HDMI audio: up to 7.1 channel /192kHz PCM, up to 5.1 channel DSD, Bitstream
- HDMI video: UHD 23.976/25/30/50/59.94/60hz, 1080 I/P, 720P, 576i/P, 480i/P, source direct.

^Analog audio characteristics

- Frequency range: HI-FI 2 channel: 20Hz~80kHz ($\pm 0.03\text{dB}$); multichannel: 20Hz~80kHz ($\pm 0.05\text{dB}$)
- Signal-to-noise ratio: $\geq 120\text{dB}$ (2CH RCA); $\geq 130\text{dB}$ (2CH XLR)
- Distortion plus noise: $\leq 0.0005\%$
- Output amplitude: (RCA) $2.1 \pm 0.2\text{Vrms}$. (XLR) $4.2 \pm 0.4\text{Vrms}$
- Dynamic range: $\geq 120\text{dB}$ (2CH RCA); $\geq 130\text{dB}$ (2CH XLR)
- Channel resolution: $\geq 110\text{dB}$ (2CH RCA); $\geq 140\text{dB}$ (2CH XLR)

^General specification

- Power supply: AC 110-120V ~ 50/60Hz / AC 220-240V ~ 50/60Hz
- Power consumption: <40W, Standby<0.5W
- Dimensions: 445 x 321 x 133 mm
- Weight: 15.4kg
- Operating Temperature: 5°C~ 35°C (41°F ~ 95°F)
- Operating Humidity: 15% ~ 75%